



SILTEX 800

D1

VERSION: 210930
Page: 1/2

PREMIUM HS STONE CHIP

DEFINITION

HS Stone chip protector of high performance suitable for applications over visible, as well as non visible parts of bodyworks which require reproducing the quality level of the original application.






Its formulation provides a great flexibility level, what makes it perfect for anticorrosive protection and protection against impacts in parts as underbodies and wheel wells. Besides, guarantees an optimal soundproofing in applications over parts with a high level of vibrations as doors, boots, or panels.

Once dry, the excellent texture created in the finish of **SILTEX 800**, allows it to be painted with bodywork basecoat paints, achieving a perfect gloss level.




PHYSICAL CHARACTERISTICS

Nature:	Elastomers and synthetic resins
Colour:	Grey, black, white
Specific weight:	1,5 kg/l at 20°C
Dry film thickness:	150-200 microns 1 coat
Yield:	5-7 m ² /Kg
VOC:	410 g/l
Solid content:	72 %

METHOD OF APPLICATION

				
Shake 30" before using	RB1 schutz gun	3-4 kg/cm ²	15-25	1-2
	HP cannister gun	2 kg/cm ²		

DRYING TIMES

		
10°C	2h	90'
20°C	1,5h	60'
30°C	1h	45'

REMARKS

The product is ready to use and it does not require additional thinner.

Shake before using.

Apply to grease and rust-free surfaces.

Avoid any mechanical action against the treated parts before 24 hours (for example: car wash with high pressure hot water).

The product is not repaintable with single layer paints or 2K varnishes..

EQUIPMENT CLEANING

Clean the equipment with a cleaning thinner before the pot life has expired.

SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

GUARANTEE

One year in unopened original packaging.

These products are for professional use only. The Safety Data Sheet should be consulted before use and the precautionary warnings on the product packaging should be observed. Its correct use, according to its purpose and respecting its technical and security data, provided in these documents, is the sole and exclusive responsibility of the user. ROBERLO S.A.U declines any liability due to the incorrect use of any product.

The information included in this documentation is based on our scientific and technical knowledge on the date of its issuance. ROBERLO S.A.U reserves the right to modify and/or discontinue all or part of the information at any time and without prior notice. It is the user's responsibility to verify the update of the information. The latest version of this document replaces all previous versions.

*All clauses contained herein apply to any future changes or modifications.
For any additional technical information please consult with our Customer Service or our Technical Department.*