



ROBERCAR

F10VERSION: 141103
Page: 1/1**ABRASIVE PASTE**

DEFINITION

ROBERCAR is a high-performance abrasive paste that has a very creamy texture. This makes it particularly suitable for manual work as it offers excellent cutting and finishing levels. Similarly, in machine polishing processes it provides an excellent balance between speed and results.

Depending on the level of shine required, it might be advisable to finish the process with the liquid polish UF-92 which is also part of our **Robercar range**.

PHYSICAL CHARACTERISTICS

Colour:	White
Specific weight:	1,3 kg/l at 20°C
Aspect:	Creamy

APPLICATION

- Sand the areas to be polished with fine abrasives from P1500 to P2000, or finer.
- Clean thoroughly the surface before polish.
- Polish by hand with a piece of cotton, or by machine spread the product on a foam or a lambswool pad and apply it at low speed 500 rpm. While polishing, increase the speed to 2000 rpm maximum until all defects have been removed.
- Clean the surface with a microfiber or a clean cloth for the elimination of product that may remain.

SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

GUARANTEE

In unopened original packaging, one year from manufacturing date.

For any technical information contact with our Customer Attention Service or our Technical Department.
ROBERLO SA declines any responsibility due to an incorrect use of the product.